

Mini Bulletin XR15Y

WorkCentre 4260 30.105.37.00

Release Date: Jun 26, 2015

Version 1.0

Software Release Details

If your software is higher or equal to the versions listed below no action is needed. Otherwise, please review this bulletin and consider taking actions as suggested.

System Software	WC 4260
System Software	30.105.37.000
Main Controller	2.50.05.371
Image Output Terminal	0.41.69
User Interface	0.040.17.005
Network Controller	4.02.14
Document Feeder	1.04

Purpose

This Bulletin is ONLY intended for the specific security problem(s) identified below. The problem(s) identified has been rated as a criticality level of **IMPORTANT**

- Includes fix for SSLv3.0 Poodle Vulnerability (CVE-2014-3566)
- Includes fix for FREAK Vulnerability In OpenSSL (CVE-2015-0204)

Installation Notes

The SPAR Software is located at:

<http://www.support.xerox.com/support/workcentre-4260/file-download/enca.html?contentId=100495>

The installation instructions are located at:

https://www.xrqsn.com/admin/public/3452/WC4260-Installation_Instructions.pdf

Save the file to a convenient location on your workstation. Unzip the file if necessary

IMPORTANT – Read before installing Firmware

The “TLS Only” or “Only TLS” checkbox will be enabled by default and will support TLS versions 1.2, 1.1 and 1.0.

- When choosing TLS only – SSL (all versions) are turned off and device is only transferring in TLS 1.2, 1.1 and 1.0.
- If “TLS Only” or “Only TLS” is unchecked, the device will use SSL (v1 or v2) and TLS (all versions) simultaneously if needed.