

Notice

This document describes the locations, capacities and contents of volatile and non-volatile memory devices within the Xerox EX260 Fiery Server.

The context of the information in this document is that normal means of access or data extraction are being attempted in order to reproduce, individuals or organizations with advanced skills or through the use of extraordinary resources and measures or specialty equipment not normally available in the industry or to the public.

The content of this document is provided for information purposes only. Performance of the products referenced herein is exclusively subject to the applicable Xerox Corporation terms and conditions of sale and/or lease. Nothing stated in this document constitutes the establishment of any additional agreement or binding obligations between Xerox Corporation and any third party.

Primary Signature Block

This evaluation and summary was completed by:

Signature	Addle
Printed Name	Brian Dahlquist
Job Title	Sr. Program Manager, Hardware Platform Development
Job Function	Responsible for EFI Platform Hardware
Preparation Date	12/2/09

Optional Signature Block

Signature	
Printed Name	
Job Title	
Job Function	
Preparation Date	

Copyright 2006, 2008 Xerox Corporation

Copyright protection claimed includes all forms and matters of copyrighted material and information now allowed by statutory or judicial law or hereinafter granted, including without limitation, material generated from the software programs that are displayed on the screen such as styles, templates, icons, screen displays, looks, etc. XEROX®, The Document Company® and all Xerox product names and product numbers mentioned in this publication are trademarks of XEROX CORPORATION. All non-Xerox brands and product names may be trademarks or registered trademarks of the respective companies, and are hereby acknowledged.

Product appearance, build status and/or specifications are subject to change without notice.

Xerox EX260 Server, XC PN 097N01745 EFI PN 45079483

Introduction

The Xerox EX260 Fiery Server is used to perform the following tasks when attached to the Xerox Copier:

Network Printing and Scanning

This document describes the amounts and types of memory contained in the device in an easy to read tabular format. To allow security issues to be addressed as needed, specific commentary has been included about job data and where Personally Identifiable Information (PII) can be found in the system.

For larger Xerox systems that may contain multiple media feeders or multiple finishers, tabulated data is shown even though these devices never contain any job or PII data in electronic form. Also, in larger Xerox systems, another vendor may supply a Digital Front End (DFE) that is connected to the Xerox Print Engine. In these cases, the vendor of the DFE must provide their own Statement of Volatility for the hardware which comprises their additions to Xerox products.

The information contained in this document has been verified at the time the product is released for sale. Manufacturing process changes may require that memory amounts are increased but, the purpose or contents of the memory will not change.

General Memory Information

Volatile Memory

All volatile memory listed is cleared after power is removed (decay occurs generally within 20 seconds at room temperature).

All volatile memory listed is required for normal system operation and during service and diagnostic procedures.

Removal of any volatile memory will void the warranty.

Non-Volatile Memory

All non-volatile memory listed is required for normal system operation and during service and diagnostic procedures.

Removal of any non-volatile memory will void the warranty.

All non-volatile memory cannot be accessed by accidental keystrokes (with exception of BIOS access keys).

Hard Drive Information

	1st	Hard Dri	ve / Partition Desc	cription	
Complete this table if th	e device has medio	a storage c	apability		
Drive / Partition (System, Image):	Removable Y/N	Size:	User Modifiable: Y/N	Function:	Process to Sanitize:
Main System Drive	N	160 GB	Υ	System	Reinstall SW (which causes a reformat)
Additional Information: partition contains OS, E				or service only and	contains no data, D

System Descriptions

Volatile Memory					
Type (SRAM, DRAM, etc)	Size	User Modifiable (Y/N)	Function or Use	Process to Sanitize	
DRAM	1 GB	Yes	Main System Memory	Power Off Server	
SDRAM	32MB	Yes	Video Memory	Power Off Server	

Non-Volatile Memory					
Type (Flash, EEPROM, etc)	Size	User Modifiable (Y/N)	Function or Use	Process to Sanitize	
BIOS	1 Mb	N	BIOS Functions	Service operation which will flash new image.	
CMOS NVRAM	256 Bytes	N	BIOS Settings Storage	Remove System Battery for 30 seconds	

Media and Storage Complete this table if the device has media storage capability					
					Type (disk drives, tape drives, CF/SD/XD memory cards, etc.):
N/A					
Additional Information:					

USB				
Complete an entry for each USB port				
USB port and location	Purpose			
4 Ports on I/O, 2 Ports on Front Bezel, 4 Ports Internally on MB	General Purpose, external ports are user accessible, internal ports are not. BIOS settings do not allow booting from the USB port.			

RFID Devices			
Complete an entry for each RFID tag *			
RFID Tag location Purpose			
N/A	No RFID devices present		