



# Statement of Volatility

Xerox<sup>®</sup> FreeFlow<sup>®</sup> Print Server Integrated for the  
Xerox<sup>®</sup> Color C60/C70 Printer



Copyright 2006, 2008, 2009, 2010, 2011, 2012, 2013, 2014 Xerox Corporation

Copyright protection claimed includes all forms and matters of copyrighted material and information now allowed by statutory or judicial law or hereinafter granted, including without limitation, material generated from the software programs that are displayed on the screen such as styles, templates, icons, screen displays, looks, etc.

XEROX®, The Document Company® and all Xerox product names and product numbers mentioned in this publication are trademarks of XEROX CORPORATION. All non-Xerox brands and product names may be trademarks or registered trademarks of the respective companies, and are hereby acknowledged.


Product appearance, build status and/or specifications are subject to change without notice.




# Statement of Volatility

Xerox® FreeFlow® Print Server Integrated for the Xerox® Color C60/C70 Printer

This evaluation and summary was completed by:

Signature	
Printed Name	Sivakumar Subramanian
Job Title	Manager
Job Function	FFPS Hardware Development
Preparation Date	22-May-2014

This evaluation was reviewed and approved by:

Signature	
Printed Name	Ralph H. Stoos Jr.
Job Title	Technical Program Manager
Job Function	Product Security Office
Preparation Date	22-May-2014

## Notice

This document describes the locations, capacities and contents of volatile and non-volatile memory devices within the FreeFlow® Print Server.

The context of the information in this document is that normal means of access or data extraction are being attempted in order to reproduce, read, or extract stored or latent data. This does not include attempts to reproduce, read or extract data or reverse engineer storage methods by individuals or organizations with advanced skills or through the use of extraordinary resources and measures or specialty equipment not normally available in the industry or to the public.

The content of this document is provided for information purposes only. Performance of the products referenced herein is exclusively subject to the applicable Xerox Corporation terms and conditions of sale and/or lease. Nothing stated in this document constitutes the establishment of any additional agreement or binding obligations between Xerox Corporation and any third party.

# Statement of Volatility

## Xerox® FreeFlow® Print Server Integrated for the Xerox® Color C60/C70 Printer

### Introduction

The Xerox Color C60/C70 FreeFlow® Print Server is used to perform the following tasks:

- High Speed Production Printing

The FreeFlow® Print Server is intended to be integrated to:

- Xerox Print Engine

- Xerox Print Station Interface Platform (“PC-UI”)

These modules provide the basic configuration. Depending on what is purchased, the number and types of feeders and finishers contained in the completed system can change.

This document describes the amounts and types of memory contained in the device in an easy to read tabular format. To allow security issues to be addressed as needed, specific commentary has been included about job data and where Personally Identifiable Information (PII) can be found in the system.

The information contained in this document has been verified at the time the product is released for sale. Manufacturing process changes may require that memory amounts are increased, but the purpose or contents of the memory should not change.

### General Memory Information

#### Volatile Memory

All volatile memory listed is cleared after power is removed (decay occurs generally within 20 seconds at room temperature).

All volatile memory listed is required for normal system operation and during service and diagnostic procedures.

Removal of any volatile memory will void the warranty.

#### Non-Volatile Memory

All non-volatile memory listed is required for normal system operation and during service and diagnostic procedures.

Removal of any non-volatile memory will void the warranty.

None of the non-volatile memory in the system can be accessed by accidental keystrokes.

## Xerox FreeFlow® Print Server (Digital Front End) System Descriptions

The data tables below detail the information regarding the volatile and non-volatile memory contained in the FreeFlow Print Server used on the Xerox Color C60/C70 Printer based on Dell OptiPlex XE2 SFF (G3420)

The Free Flow Print Server Digital Front End is a PC-type motherboard and an interface card. It is equipped with a BIOS, main RAM and Video memory.

Volatile Memory Descriptions				
Type (SRAM, DRAM, etc)	Size	User Modifiable (Y/N)	Function or Use	Process to Clear:
DDR3 DRAM	8GB	N	System OS RAM to contain executable code. No job data stored here persistently.	Reboot or power down system.
DRAM	3MB	N	CPU cache	Reboot or power down system

Non-Volatile Memory Descriptions				
Type (Flash, EEPROM, etc)	Size	User Modifiable (Y/N)	Function or Use	Process to Clear:
Flash EEPROM	12MB	Y with vendor-provided tool.	System BIOS. Boot code. System configuration information. No job data stored here.	Not possible, system not functional if corrupted/removed.
Battery backed (CMOS) RAM	256KB	N	BIOS settings No job data stored here.	Motherboard jumper, OR Remove power, remove battery, wait, then replace.
TPM Chip	4KB	N	Trusted Platform Module. No job data stored here.	Not possible, system not functional if corrupted/removed.

### Interface Card:

Non-Volatile Memory Descriptions				
Type (Flash, EEPROM, etc)	Size	User Modifiable (Y/N)	Function or Use	Process to Clear:
Flash EEPROM	32Mbits	N	Programmable logic configuration information. No job data stored here.	Not possible, system not functional if corrupted/removed.

## Xerox FreeFlow® Print Server (Digital Front End) System Descriptions (continued)

The data tables below detail the information regarding the storage devices contained in the FreeFlow® Print Server.

Hard Disk Descriptions					
Complete this table if the device has media storage capability					
Drive / Partition (System, Image):	Removable Y / N	Size:	User Modifiable: Y / N	Function:	Process to Clear:
System Disk	Y	1TB	N with normal operation	Operating System, Fonts, configuration file storage	Diagnostic Procedure
<p><b>Additional Information:</b>                      The System Disk (C drive) contains the Windows Operating System and store executable, fonts, and settings files. During normal operation, job files remain stored on the data partition (D drive) until completed or removed. Under typical system usage job images may also be stored temporarily on the data partition. The total size of the HDD is 1TB and the approximate usage of the disk by Operating System and application software is 35GB. However the usage size for “data” and “outQ” partition can increase while running the Free Flow® Software.</p> <p>Images are stored in a proprietary encoded format and fragments of the job data are stored at random locations in the data partition. Free Flow® has a data overwrite tool and not a disk overwrite tool. The data overwrite tool wipes out only customer Job image and data. It is based on “DoD 5220.22-M” algorithm and it will not wipe out the entire disk, merely area that contain job images..</p>					

USB Port(s)	
Complete an entry for each USB port	
USB port and location	Purpose
Front of FreeFlow® Print Server: 2 USB2.0 ports, 2 USB 3.0 ports	User stores scanned files of job files on Flash Media. Physical security of this information is the responsibility of the user or operator.
Back of FreeFlow® Print Server: 4 USB2.0 ports , 2 USB3.0 ports	User stores scanned files of job files on Flash Media. Physical security of this information is the responsibility of the user or operator.
<p><b>Additional Information:</b>                      A number of devices can be connected to USB ports on the FreeFlow Print Server system. Once information has been copied (either as a back-up data set or as a transfer medium), physical security of this information is the responsibility of the user or operator.</p>	

RFID Devices	
Complete an entry for each USB port	
RFID Device	Purpose
N/A	N/A