Statement of Volatility
WorkCentre 6025

Statement of Volatility
WorkCentre 6025

Notice

This document describes the locations, capacities and contents of volatile and non-volatile memory devices within the WorkCentre 6025.

The context of the information in this document is that normal means of access or data extraction are being attempted in order to reproduce, read, or extract stored or latent data. This does not include attempts to reproduce, read or extract data or reverse engineer storage methods by individuals or organizations with advanced skills or through the use of extraordinary resources and measures or specialty equipment not normally available in the industry or to the public.

The content of this document is provided for information purposes only. Performance of the products referenced herein is exclusively subject to the applicable Xerox Corporation terms and conditions of sale and/or lease. Nothing stated in this document constitutes the establishment of any additional agreement or binding obligations between Xerox Corporation and any third party.

This evaluation and summary was certified by:

Signature	
Printed Name	Ralph H. Stoos Jr.
Job Title	Technical Program Manager
Job Function	Technical Program Manager, Office of the CTO
Preparation Date	1/12/2015

Statement of Volatility
WorkCentre 6025

Introduction

The WorkCentre 6025 is used to perform the following tasks:

Printing

Copying

Scanning

This document describes the amounts and types of memory contained in the device in an easy to read tabular format. To allow security issues to be addressed as needed, specific commentary has been included about job data and where Personally Identifiable Information (PII) can be found in the system.

The information contained in this document has been verified at the time the product is released for sale. Manufacturing process changes may require that memory amounts are increased but, the purpose or contents of the memory should not change.

General Memory Information

Volatile Memory

All volatile memory listed is cleared after power is removed (decay occurs generally within 20 seconds at room temperature).

All volatile memory listed is required for normal system operation and during service and diagnostic procedures.

Removal of any volatile memory will void the warranty.

Non-Volatile Memory

All non-volatile memory listed is required for normal system operation and during service and diagnostic procedures.

Removal of any non-volatile memory will void the warranty.

None of the non-volatile memory in the system can be accessed by accidental keystrokes.

Device Module Descriptions

Signature Block

This evaluation and summary was completed by:

Signature	
Printed Name	John Scriven
Job Title	SW Technical Program Manager
Job Function	SW Technical Program Manager
Preparation Date	1/12/2015

The data tables below detail the information regarding the volatile and non-volatile memory contained in the WorkCentre 6025 print engine.

Volatile Memory Description

Type (SRAM, DRAM, etc)	Size	User Modifiable (Y/N)	Function or Use	Process to Clear:
SDRAM	256MB	N	System Memory, Executable code, Printer control data	Power Off System

Additional Information:
All memory listed above contains code for execution and configuration information. No user or job data is stored in these locations.

Non-Volatile Memory Description

Type (Flash, EEPROM, etc)	Size	User Modifiable (Y/N)	Function or Use	Process to Clear:
Flash	16MB	N	Firmware, Color Tables, User and System Parameters	N/A

Additional Information:
All memory listed above contains code for execution and configuration information. No user or job data is stored in these locations.

Hard Disk Descriptions

Complete this table if the device has media storage capability

Drive / Partition (System, Image):	Removable Y / N	Size:	User Modifiable: Y / N	Function:	Process to Clear:
N/A no HDD					

Additional Information:

Media and Storage Descriptions

Type (disk drives, tape drives, CF/SD/XD memory cards, etc.):	Removable Y / N	Size:	User Modifiable: Y / N	Function:	Process to Clear:

Additional Information:

USB Port(s)

Complete an entry for each USB port

USB port and location	Purpose
USB 2.0 port	Enables computer connectivity for printing and scanning.
Front Panel USB Port	Enables scanning to and printing from USB devices.

Additional Information:
USB 2.0 port (rear) can be disabled

Feeder and Finisher Module Descriptions

The text below details the information regarding the volatile and non-volatile memory contained in the WorkCentre 6025 supported feeders. This document lists the available options. Depending on the configuration purchased, your system will contain on or more of these devices. **NOTE: None of these devices store any job data in electronic form.**

Feeder Module Descriptions

The WorkCentre 6025 does not offer any standard or optional feeder modules.

Finisher Module Descriptions

The WorkCentre 6025 does not offer any standard or optional finishing modules.